

# Reflux 819/FO

The **Reflux 819/FO** is one of the **pilot-operated gas pressure regulators** designed and manufactured by Pietro Fiorentini. This device is suitable for use with previously filtered non-corrosive gases, and it is mainly used for high-pressure transmission systems, power plants and for medium pressure natural gas distribution networks. According to the European Standard EN 334, it is classified as **Fail Open**. The Reflux 819/FO is **Hydrogen Ready** for NG-H2 blending.



Gas liquefaction



City gates



Power generation

Gas compression /  
booster stations

Heavy industries



LNG marine



Gas storage



Regasification



Gas reverse-flow

Features	Values
Design pressure* (PS <sup>1</sup> / DP <sup>2</sup> )	up to 10.2 MPa up to 1,479 psig
Ambient temperature* (TS <sup>1</sup> )	from -20 °C to +60 °C from 4 °F to +140 °F
Inlet gas temperature*	from -20 °C to +60 °C from 4 °F to +140 °F
Inlet pressure (MAOP / p <sub>umax</sub> <sup>1</sup> )	from 0.3 MPa to 10.2 MPa from 43.5 psig to 1,479 psig
Range of downstream pressure (Wd <sup>1</sup> )	from 0.1 MPa to 7.4 MPa from 14.5 psig to 1,073 psig
Available accessories	DB/819 Silencer, LDB/171 Silencer, PM/819 Monitor, SB/82 Slam shut, HB/97 Slam shut
Minimum operating differential pressure (Δp <sub>min</sub> <sup>1</sup> )	0.2 MPa   29 psig
Accuracy class (AC <sup>1</sup> )	up to 2.5
Lock-up pressure class (SG <sup>1</sup> )	up to 5
Nominal size (DN <sup>1,2</sup> )	DN 25   1"; DN 50   2"; DN 80   3"; DN 100   4"; DN 150   6"; DN 200   8"; DN 250   10"; DN 300   12"
Connections	Class 150, 300, 600 RF or RTJ according to ASME B16.5 and PN16

(<sup>1</sup>) according to EN334 standard

(<sup>2</sup>) according to ISO 23555-1 standard

(\*) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.

**Table 1** Features

## Materials and Approvals

Part	Material
Body	ASTM A 352 LCC cast steel for classes ANSI 600 and 300; ASTM A 216 WCB cast steel for classes ANSI 150 and PN 16/40
Heads	ASTM A 350 LF2 steel
Stem	AISI 416 stainless steel
Plug	ASTM A 350 LF2 nickel-plated steel
Seat	Vulcanized Nitrile Rubber on metal support
Membrane	Rubberised Canvas (pre-formed by hot-pressing process)
O-rings	Nitrile Rubber
Compression fittings	Made of zinc-plated steel according to DIN 2353; on request, stainless steel

**NOTE:** The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.

**Table 2** Materials

The **Reflux 819/FO** regulator is designed according to the European standard EN 334.

The regulator reacts in opening (Fail Open) according to EN 334.

The product is certified according to European Directive 2014/68/EU (PED).

DVGW certified as a truly Fail Open regulator.

Leakage class: bubble tight, better than VIII according to ANSI/FCI 70-3.



EN 334



PED-CE



DVGW

## Reflux 819/FO competitive advantages



Compact and simple design



High accuracy



1:1000 High turn-down ratio



True Fail Open plug and seat regulator



Built-in pilot filter



Top Entry



Easy maintenance



Built-in accessories



Biomethane compatible and  
20% Hydrogen blending compatible.  
Higher blending available on request



Balanced type