

Reflux 819/FO

The **Reflux 819/FO** is one of the **pilot-operated gas pressure regulators** designed and manufactured by Pietro Fiorentini. This device is suitable for use with previously filtered non-corrosive gases, and it is mainly used for high-pressure transmission systems, power plants and for medium pressure natural gas distribution networks. According to the European Standard EN 334, it is classified as **Fail Open**. The Reflux 819/FO is **Hydrogen Ready** for NG-H2 blending.



- | | | |
|--|--|--|
|  Gas liquefaction |  City gates |  Power generation |
|  Gas compression / booster stations |  Heavy industries |  LNG marine |
|  Gas storage |  Regasification |  Gas reverse-flow |

Features	Values	
Design pressure* (PS ¹ / DP ²)	up to 10.3 MPa up to 1500 psig	
Ambient temperature* (TS ¹)	Standard version from -10 °C to +70 °C from +14 °F to +158 °F	Arctic version from -40 °C to +65 °C from -40 °F to +150 °F
Inlet gas temperature*	Standard version from -10 °C to +70 °C from +14 °F to +158 °F	Arctic version from -20 °C to +60 °C from -4 °F to +140 °F
Inlet pressure (MAOP / p _{umax} ¹)	from 0.3 to 10.2 MPa (for CE marked product it is limited to 10.0 MPa) from 43.5 to 1480 psig (for CE marked product it is limited to 1450 psig)	
Range of downstream pressure (Wd ¹)	from 0.1 to 7.4 MPa from 145 to 1073.3 psig	
Available accessories	DB/819 Silencer, LDB/171 Silencer, PM/819 Monitor, SB/82 Slam shut, HB/97 Slam shut	
Minimum operating differential pressure (Δp _{min} ¹)	0.2 MPa 29 psig	
Accuracy class (AC ¹)	up to 2.5% gauge	
Lock-up pressure class (SG ¹)	up to 5% gauge	
Nominal size (DN ^{1,2})	DN 25 1"; DN 50 2"; DN 80 3"; DN 100 4"; DN 150 6"; DN 200 8"; DN 250 10"; DN 300 12"	
Connections	Class 150, 300, 600 RF or RTJ according to ASME B16.5 and PN16	

(¹) according to EN334 standard

(²) according to ISO 23555-1 standard

(*) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.

Table 1 Features

Materials and Approvals

Part	Material
Body	ASTM A 352 LCC cast steel for classes ANSI 600 and 300; ASTM A 216 WCB cast steel for classes ANSI 150 and PN 16/40
Heads	ASTM A 350 LF2 steel
Stem	AISI 416 stainless steel
Plug	ASTM A 350 LF2 nickel-plated steel
Seat	Vulcanized Nitrile Rubber on metal support
Membrane	Rubberised Canvas (pre-formed by hot-pressing process)
O-rings	Nitrile Rubber
Compression fittings	Made of zinc-plated steel according to DIN 2353; on request, stainless steel

NOTE: The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.

Table 2 Materials

The **Reflux 819/FO** regulator is designed according to the European standard EN 334.

The regulator reacts in opening (Fail Open) according to EN 334.

The product is certified according to European Directive 2014/68/EU (PED).

DVGW certified as a truly Fail Open regulator.

Leakage class: bubble tight, better than VIII according to ANSI/FCI 70-3.



EN 334



PED-CE



DVGW

Reflux 819/FO competitive advantages



Compact and simple design



High accuracy



High turn-down ratio



True Fail Open plug and seat regulator



Built-in pilot filter



Top Entry



Easy maintenance



Built-in accessories



Biomethane compatible and
20% Hydrogen blending compatible.
Higher blending available on request



Balanced type