

Reval 182

The **Reval 182** is one of the **pilot-operated gas pressure regulators** designed and manufactured by Pietro Fiorentini. This device is suitable for use with previously filtered non-corrosive gases, and it is mainly used for medium and low pressure natural gas distribution networks. According to the European Standard EN 334, it is classified as **Fail Close**.



Gas engines



Medium/small industry



District stations

Features	Values
Design pressure* (PS ¹ / DP ²)	up to 2.5 MPa up to 362 psig
Ambient temperature* (TS ¹)	from -20 °C to +60 °C from -4 °F to +140 °F
Inlet gas temperature*	from -20 °C to +60 °C from -4 °F to +140 °F
Inlet pressure (MAOP / p _{umax} ¹)	from 0.02 to 2.5 MPa from 2.9 psig to 362 psig
Range of downstream pressure (Wd ¹)	from 0.7 KPa to 1.2 MPa from 2.81" w.c. to 174 psig
Available accessories	DB/182 Silencer, PM/182 Monitor, SB/82 Slam shut, SA Slam shut HB/97 Slam shut, opening indicator
Minimum operating differential pressure (Δp _{min} ¹)	0.01 MPa 1.45 psig
Accuracy class (AC ¹)	up to 2.5
Lock-up pressure class (SG ¹)	up to 5
Nominal size (DN ^{1,2})	DN 25 1"; DN 50 2" DN 65 2" 1/2; DN 80 3"; DN 100 4"; DN 150 6"; DN 200 8"; DN 250 10"
Connections	Class 150 RF or RTJ according to ASME B16.5 and PN16, 25 and 40 according to ISO 7005

(¹) according to EN334 standard
(²) according to ISO 23555-1 standard
(*) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.

Table 1 Features

Materials and Approvals

Part	Material
Body	Cast steel ASTM A216 WCB for all sizes Ductile iron GS 400-18 ISO 1083 for Size ≤ 8"
Heads	Die stamped carbon steel
Stem	AISI 416 Stainless steel
Plug	ASTM A 350 LF2 Nickel coated on sealing surfaces
Seat	Steel + vulcanized rubber
Diaphragm	Rubberized canvas
O-rings	Nitrile Rubber
Compression fittings	In zinc-plated carbon steel according to DIN 2353 Stainless steel on request

NOTE: The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.

Table 2 Materials

The **Reval 182** regulator is designed according to the European standard EN 334. The regulator reacts in closing (Fail Close) according to EN 334. The product is certified according to European Directive 2014/68/EU (PED). Leakage class: bubble tight, better than VIII according to ANSI/FCI 70-3.



EN 334



PED-CE

Reval 182 competitive advantages



Compact and simple design



Top Entry



High accuracy



Easy maintenance



1:500 High turn-down ratio



In-built accessories



Fail Close plug and seat regulator



Balanced type



Built-in pilot filter



Biomethane compatible and 20% Hydrogen blending compatible. Higher blending available on request